TIME-SERT® Removable Thread locker p/n 2155

Page 1/8

Safety Data Sheet acc. to OSHA HCS

Printing date 03/06/2019 Reviewed on 02/28/2019

1 Identification

- Product identifier

- Trade name: TIME-SERT® Removable Thread locker

- Synonyms: 2155 Removable Thread locker

- **Part number:** 2155

- Application of the substance / the mixture Thread locker

- Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Time Fastener Co. 5301 Longley Lane Lane Unit G Reno Nevada

USA

Telephone: 1 775 829-1026 Email: contact01@timesert.com Website: www.timesert.com

- Information department: Product safety department

- Emergency telephone number:

United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard(s) identification

Classification of the substance or mixture



GHS08 Health hazard

H351 Suspected of causing cancer. Carc. 2

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS07 GHS08

- Signal word Warning

- Hazard-determining components of labeling:

2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate methacrylic acid, monoester with propane-1,2-diol dimethylbenzyl hydroperoxide 2'-phenylacetohydrazide

- Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash face, hands and any exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area. P271

Reviewed on 02/28/2019

TIME-SERT® Removable Thread Locker

(Contd. of page 1)

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.
P314 Get medical advice/attention if you feel unwell.

P362+P364
P332+P313
P333+P313
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1 Reactivity = 0

- HMIS-ratings (scale 0 - 4)



Health = *2
Fire = 1
Reactivity = 0

- Other hazards

- Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous	components:	
CAS: 25852-47-5	2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	50 – 59%
CAS: 27813-02-1	methacrylic acid, monoester with propane-1,2-diol Eye Irrit. 2A, H319; Skin Sens. 1, H317	5 – 9%
CAS: 67762-90-7	Amorphous Silica Combustible Dust	1 – 4%
CAS: 80-15-9	dimethylbenzyl hydroperoxide Self-react. F, H242; Org. Perox. E, H242; Acute Tox. 3, H311; STOT RE 2, H373; Asp. Tox. 1, H304; Eye Dam. 1, H318; Acute Tox. 4, H302; STOT SE 3, H335; Flam. Liq. 4, H227	1 – 4%
CAS: 114-83-0	2'-phenylacetohydrazide Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	≤ 1%
CAS: 98-82-8	Cumene Flam. Liq. 3, H226; Carc. 2, H351; Asp. Tox. 1, H304; Acute Tox. 4, H302; STOT SE 3, H335	≤ 1%

4 First-aid measures

- Description of first aid measures

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation. Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed
 No further relevant information available.

Reviewed on 02/28/2019

TIME-SERT® Removable Thread Locker

(Contd. of page 2)

5 Fire-fighting measures

- Extinguishing media

- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

CO2, sand, extinguishing powder. Do not use water.

- For safety reasons unsuitable extinguishing agents: Water

- Special hazards arising from the substance or mixture No further relevant information available.

- Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

No special precautions are necessary if used correctly.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities

- Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.

Control parameters

- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

CAS: 8	30-15-9 dimethylbenzyl hydroperoxide
WEEL	Long-term value: 6 mg/m³, 1 ppm Skin
CAS: 9	98-82-8 cumene
PEL	Long-term value: 245 mg/m³, 50 ppm Skin
REL	Long-term value: 245 mg/m³, 50 ppm Skin
TLV	Long-term value: (246) NIC-0.5 mg/m³, (50) NIC-0.1 ppm NIC-A3

Printing date 03/06/2019

Reviewed on 02/28/2019

TIME-SERT® Removable Thread locker

- Additional information: The lists that were valid during the creation were used as basis.

(Contd. of page 3)

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber. NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:

9 Physical and chemical properties



Tightly sealed goggles

- Body protection: Protective work clothing

3 Physical and Chemical properties	
- Information on basic physical and che - General Information - Appearance:	emical properties
- Form:	Liquid
- Color:	Blue
- Odor:	Characteristic
- Odor threshold:	Not determined.
- pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. ≥ 200 °C (≥ 392 °F)
- Flash point:	95 ℃ (203 ℉)
- Flammability (solid, gaseous):	Not applicable.
 Decomposition temperature: 	Not determined.
- Auto igniting:	Product is not selfigniting.
- Danger of explosion:	Product does not present an explosion hazard.
- Explosion limits: - Lower: - Upper:	Not determined. Not determined.
- Vapor pressure at 20 ℃ (68 ℉):	n.a. hPa
- Density at 20 °C (68 °F): - Relative density - Vapor density - Evaporation rate	~ 1.07 g/cm³ (~ 8.92915 lbs/gal) Not determined. Not determined. Not determined.

Printing date 03/06/2019

Reviewed on 02/28/2019

TIME-SERT® Removable Thread locker

(Contd. of page 4)

- Solubility in / Miscibility with - Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octano	
- Viscosity:	
- Dynamic:	Not determined.
- Kinematic:	Not determined.
- Solvent content:	
 Organic solvents: 	0.6 %
- Water:	1.3 %
- VOC content:	0.64 %
	~ 6.8 g/l / ~ 0.06 lb/gal
- Solids content:	86.5 %
- Other information	No further relevant information available.

10 Stability and reactivity

- *Reactivity* No further relevant information available.
 - Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

Aldehyde Hydrocarbons

11 Toxicological information

- Information on toxicological effects
 - Acute toxicity:

- LI	- LD/LC50 values that are relevant for classification:		
ATE (Acu	ATE (Acute Toxicity Estimate)		
Oral	LD50	5,991 mg/kg (rat)	
Dermal	LD50	29,467 mg/kg (rat)	
Inhalative	LC50/4 h	12,966 mg/l (rat)	
CAS: 80-1	5-9 dimet	hylbenzyl hydroperoxide	
Oral	LD50	382 mg/kg (rat)	
Dermal	LD50	500 mg/kg (rat)	
Inhalative	LC50/4 h	220 mg/l (rat)	
CAS: 114-	CAS: 114-83-0 2'-phenylacetohydrazide		
Oral	LD50	270 mg/kg (mouse)	
CAS: 98-8	CAS: 98-82-8 cumene		
Oral	LD50	1,400 mg/kg (rat)	
Dermal	LD50	12,300 mg/kg (rabbit)	
Inhalative	LC50/4 h	24.7 mg/l (mouse)	
	D	invitant affact.	

- Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)		
CAS: 98-82-8	cumene	2B
CAS: 13463-67-7	titanium dioxide	2B
CAS: 111-76-2	2-butoxyethanol	3

Printing date 03/06/2019

Reviewed on 02/28/2019

TIME-SERT® Removable Thread

	(Contd. of page 5)
- NTP (National Toxicology Program)	
CAS: 98-82-8 cumene	R
CAS: 130-15-4 1,4-naphthoquinone	R
- OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- Toxicity
 - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.
- Additional ecological information:
 - General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
 - **PBT:** Not applicable.
 - vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
 - Recommendation: Disposal must be made according to official regulations.

14 Transport information		
- UN-Number	and an analysis of	
- DOT, ADN, IMDG, IATA	not regulated	
 UN proper shipping name DOT, ADN, IMDG, IATA 	not regulated	
- Transport hazard class(es)		
- DOT, ADN, IMDG, IATA - Class	not regulated	
- Packing group - DOT, IMDG, IATA	not regulated	
- Environmental hazards:		
- Marine pollutant:	No	
- Special precautions for user	Not applicable.	
- Transport in bulk according to Annex II of	MARPOL73/78	
and the IBC Code	Not applicable.	
- UN "Model Regulation":	not regulated	

*15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture - Sara

- Se	ection 355 (extremely hazardous substances):		
None of the in	None of the ingredients is listed.		
- Se	- Section 313 (Specific toxic chemical listings):		
CAS: 80-15-9	dimethylbenzyl hydroperoxide		
CAS: 98-82-8	cumene		
CAS: 111-76-2	2-butoxyethanol		

Printing date 03/06/2019

Reviewed on 02/28/2019

TIME-SERT® Removable Thread locker

(Contd. of page 6) - TSCA (Toxic Substances Control Act): 2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate Tetraethylene glycol hexoate methacrylic acid, monoester with propane-1,2-diol Amorphous Silica dimethylbenzyl hydroperoxide Saccharin propane-1,2-diol 2'-phenylacetohydrazide cumene 2-Phenyl-2-propanol titanium dioxide tetrasodium ethylenediaminetetraacetate N-isopropylhydroxylamine 1,4-naphthoquinone Colorant Alumina Trihydrate 2-Propanone, oxime 2,4,7,9-tetramethyldec-5-yne-4,7-diol 2-butoxyethanol Deionized water - TSCA new (21st Century Act): (Substances not listed) CAS: 25852-47-5 | 2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate CAS: 114-83-0 2'-phenylacetohydrazide - Hazardous Air Pollutants CAS: 98-82-8 cumene CAS: 130-15-4 1,4-naphthoguinone

- Proposition 65

- Chemicals known to cause cancer:

CAS: 98-82-8 cumene

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories

- EP	A (Environmental Protection Agency)		
CAS: 98-82-8	cumene	D,	CBD
CAS: 111-76-2	2-butoxyethanol	NL	
- TL	/ (Threshold Limit Value established by ACGIH)	<u>'</u>	
CAS: 13463-67	7 titanium dioxide		A4
CAS: 111-76-2	2-butoxyethanol		АЗ
- NIC	OSH-Ca (National Institute for Occupational Safety and Health)		
CAS: 13463-67	7 titanium dioxide		

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Time Fastener Co., Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
 - Date of preparation / last revision 03/06/2019 / 59
 - Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. of page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 02/28/2019

TIME-SERT® Removable Thread locker

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Flam. Liq. 4: Flammable liquids – Category 4 Self-react. F: Self-reactive substances and mixtures – Type E/F Org. Perox. E: Organic peroxides – Type E/F Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2 SKin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (repeated exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that Time Fastener Co., Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and Time Fastener Co. Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

TIME-SERT® is a registered trademark of Time Fastener Co.