Safety Data Sheet acc. to OSHA HCS

Printing date 09/28/2015 Reviewed on 08/25/2015

1 Identification

- Product identifier

- Trade name: TIME-SERT® Threadlocker

- Synonyms: 6020 High Temp / High Strength Threadlocker

- Part number: 6020

2 Hazard(s) identification

- Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS07

- Signal word Warning

- Hazard-determining components of labeling:

Ethoxylated dimethacrylate

- Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

- Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P280 Wear eye protection / face protection.
P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P302+P352 IF ÓN SKIN: Wash with plenty of water. P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/28/2015 Reviewed on 08/25/2015

Trade name: TIME-SERT® Threadlocker

- Classification system:

- NFPA ratings (scale 0 - 4)



Health = 1 Fire = 1Reactivity = 0

- HMIS-ratings (scale 0 - 4)



Fire = 1

- Other hazards
 - Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
 - **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dange	- Dangerous components:			
	Ethoxylated dimethacrylate	70-80%		
	Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Irrit. 2B, H320			
27813-02-1	Hydroxypropyl methacrylate	5-10%		
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319			
80-15-9	Cumene hydroperoxide	≤ 1.00%		
	Org. Perox. EF, H242; Acute Tox. 3, H331; STOT RE 2, H373; Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Flam. Liq. 4, H227			

4 First-aid measures

- Description of first aid measures

- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
 - Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
 - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

Safety Data Sheet acc. to OSHA HCS

Printing date 09/28/2015 Reviewed on 08/25/2015

Trade name: TIME-SERT® Threadlocker

See Section 13 for disposal information.

(Contd. of page 2)

7 Handling and storage

- Handling:
 - Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

No special precautions are necessary if used correctly.

- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
 - Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters
 - Components with limit values that require monitoring at the workplace:

80-15-9 Cumene hydroperoxide

WEEL Long-term value: 6 mg/m³, 1 ppm

Skin

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls
 - Personal protective equipment:
 - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties
 - General Information
 - Appearance:

- Form: Fluid - Color: Red

Safety Data Sheet acc. to OSHA HCS

Printing date 09/28/2015 Reviewed on 08/25/2015

Trade name: TIME-SERT® Threadlocker

	(Contd. of page	
- Odor:	Characteristic	
- Odour threshold:	Not determined.	
- pH-value:	Not determined.	
- Change in condition		
 Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 195 ℃ (383 ℉)	
- Flash point:	95 ℃ (203 ℉)	
- Flammability (solid, gaseous):	Not applicable.	
- Ignition temperature:		
- Decomposition temperature:	Not determined.	
- Auto igniting:	Product is not selfigniting.	
- Danger of explosion:	Product does not present an explosion hazard.	
- Explosion limits:		
- Lower:	Not determined.	
- Upper:	Not determined.	
- Vapor pressure:	Not determined.	
- Density:	Not determined.	
- Relative density	Not determined.	
- Vapour density	Not determined.	
- Evaporation rate	Not determined.	
- Solubility in / Miscibility with - Water:	Nick and a field on a fifth of the angle	
	Not miscible or difficult to mix.	
- Partition coefficient (n-octanol/wa	ter): Not determined.	
- Viscosity:		
- Dynamic:	Not determined.	
- Kinematic:	Not determined.	
- Solvent content:		
- Organic solvents:	0.8 %	
- Water:	0.1 %	
- VOC content:	0.8 %	
	8.1 g/l / 0.07 lb/gl	
- Solids content:	87.4 %	
- Other information	No further relevant information available.	

10 Stability and reactivity

- Reactivity No further relevant information available.
 - Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- **Possibility of hazardous reactions** No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

Aldehyde

Hydrocarbons

11 Toxicological information

- Information on toxicological effects
 - Acute toxicity:

- LD/LC50 values that are relevant for classification:						
80-15-9 Cumene hydroperoxide						
Oral	LD50	382 mg/kg (rat)				
Dermal	LD50	500 mg/kg (rat)				
Inhalative	LC50/4 h	220 mg/l (rat)				

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/28/2015 Reviewed on 08/25/2015

Trade name: TIME-SERT® Threadlocker

- Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.

- on the eye: Irritating effect.

- Sensitization: Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)				
85-83-6 Colorant	3			
- NTP (National Toxicology Program)				
None of the ingredients is listed.				
- OSHA-Ca (Occupational Safety & Health Administration)				
None of the ingredients is listed.				

12 Ecological information

- Toxicity
 - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.
- Additional ecological information:
 - General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
 - **Recommendation:** Disposal must be made according to official regulations.

14 Transport information	
- UN-Number - DOT, ADN, IMDG, IATA	not regulated
- UN proper shipping name - DOT, ADN, IMDG, IATA	not regulated
- Transport hazard class(es)	
- DOT, ADN, IMDG, IATA - Class	not regulated
- Packing group - DOT, IMDG, IATA	not regulated
- Environmental hazards: - Marine pollutant:	No
- Special precautions for user	Not applicable.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
- UN "Model Regulation":	not regulated
	(Contd. on page 6

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/28/2015 Reviewed on 08/25/2015

Trade name: TIME-SERT® Threadlocker

(Contd. of page 5)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- Section 355 (extremely hazardous substances): None of the ingredients is listed. - Section 313 (Specific toxic chemical listings): 80-15-9 Cumene hydroperoxide ethylene glycol - TSCA (Toxic Substances Control Act): Hydroxypropyl methacrylate Cumene hydroperoxide Propylene glycol Polyethylene glycol dimethacrylate Saccharin 2'-phenylacetohydrazide ethylene glycol Colorant Synthetic amorphous silica (fumed) 1,4-naphthoquinone

- Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

ethylene glycol

Deionized water

- Carcinogenic categories

- EPA (Environmental Protection Agency)

None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)

ethylene glycol

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Time Fastener Co., Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
 - Date of preparation / last revision 09/28/2015 / 6
 - Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 4: Flammable liquids, Hazard Category 4

Org. Perox. EF: Organic Peroxides, Types E, F Acute Tox. 4: Acute toxicity, Hazard Category 4

A4

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/28/2015 Reviewed on 08/25/2015

Trade name: TIME-SERT® Threadlocker

Acute Tox. 3: Acute toxicity, Hazard Category 3
Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1
Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that Time Fastener Co., Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and Time Fastener Co. Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

Time Fastener Co., Inc. are registered trademarks of Time Fastener Co. Incorporated, TIME-SERT® is a registered trademark of Time Fastener Co., Inc.